



## **Truck Requirements for Ace Luggers Hoists**

- Hydraulic Hoses:** Included in Ace's Price (If Ace mounts the unit on chassis)
- Hydraulic Tank:** Ace's supplies 50-gallon tank with sight gauge. **Requires 36" of clean frame rail** on driver or passenger side. If customer wants a tank other than steel(black), additional charges may occur.
- Electrical Wiring:** Ace bodies have a mid-body turn signal, please add wiring harness to accommodate. Mid body turns i.e. Body Builder Package
- Power Take-Off:** Ace prefers that the Chassis supplier mount the PTO. Ace supplies a P-51 Parker Direct mount pump (4 bolt B flange 7/8-13 spline shaft)  
If Ace is to mount PTO: Serial number and model of transmission is required. Need a in cab dash mount switch with air/wire run to side of bottom of transmission
- Tarping System:** Add 12" to Truck Frame C/T if applicable
- Lighting:** If Strobe Lights and/or Work Lights are to be installed, please include switch on dash to accommodate and have wires run to back of cab.
- Toolbox:** If being installed, please specify if **frame mount** or **body mount** and if customer wants Steel/Aluminum construction.
- In-Cab Controls:** Please allot a 10"x10" area between driver and passenger seat (if applicable) for control stand.

**Please Ship Chassis to the address below if Ace is mounting the body.**

Brother's Equipment, Inc. Team  
1335 E 171<sup>st</sup> Street  
Cleveland, OH, 44110  
800-578-8471  
216-458-0330 Fax  
Email Us: [Sales@theACEadvantage.com](mailto:Sales@theACEadvantage.com)